

Specification Sheet

BF906



NATUREFLEX WHITE

S9500

FACE:

A white high-gloss film with print receptive coating. Produced from wood pulp sourced from managed plantations, the material is biodegradable and compostable. This material is printable by flexo and rotogravure printing.

Thickness **46 micron ±5%**
Basic weight **65 gsm ±5%**

ADHESIVE:

S9500 is an acrylic based biodegradable adhesive with good initial tack and adhesion on a wide variety of substrates.

Initial Tack **Medium**
Final Adhesion **High**
Min. App.Temp **+5°C**
Temp Range **-20°C to +80°C**
UV Resistance **Moderate**

Complies with the European food regulation 1935/2004/EC for direct food contact with dry, non-fatty foodstuff. Complies with DIN EN 13432 biodegradability and compostability regulation and is OK Compost certified under the tracking number S259.

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness **53 micron ±5%**
Basic Weight **59 gsm ±5%**

SHELF LIFE:

6 months when stored at 20° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.



Unit A2, Hubert Road,
Brentwood, Essex CM14 4JE

Sales
sales@bakermaterials.co.uk

Labels
01277 281900

Materials
01277 281910

BakPac
01277 281930

bakermaterials.co.uk

Director: S R Baker. Company Reg No: 1116854 in England. Registered Office: Unit A2 Hubert Road, Brentwood, Essex CM14 4JE. VAT Reg No: GB 230 7578 65