

Specification Sheet

BM570



RECYCLED PAPER

PERMANENT

FACE:

A white, machine coated, mid gloss paper utilizing 100% recycled fibres. FSC Recycled Credit.

Suitable for flexo, offset, rotogravure and screen. Suitable for thermal transfer printing with wax/resin ribbons. Testing recommended.

Thickness 87 micron $\pm 5\%$

Basic weight 70 gsm $\pm 5\%$

ADHESIVE:

An acrylic based general permanent adhesive very good heat resistance.

Initial Tack Very High

Final Adhesion High

Min. App.Temp 0°C

Temp Range -20°C to +100°C

UV Resistance Good

LINER:

White woodfree kraft backing paper. FSC.

Thickness 54 micron $\pm 5\%$

Basic Weight 51 gsm $\pm 5\%$

SHELF LIFE:

1 year when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.



Unit A2, Hubert Road,
Brentwood, Essex CM14 4JE

Sales
sales@bakermaterials.co.uk

Labels
01277 281900

Materials
01277 281910

BakPac
01277 281930

bakermaterials.co.uk

Director: S R Baker. Company Reg No: 1116854 in England. Registered Office: Unit A2 Hubert Road, Brentwood, Essex CM14 4JE. VAT Reg No: GB 230 7578 65