Specification Sheet BM579



ROCK PAPER

PEELABLE

FACE:

A matt white durable paper-like product, manufactured from calcium carbonate (approximately 80%) bonded with high density polyethylene (HDPE, approximately 20%).

The face material can be printed by conventional printing techniques including flexo, screen, offset, letterpress, silkscreen.

Applications are predominantly in home and personal care but also where characteristics such as durabillity and matt appearance are required.

Thickness	100 micron ±5%
Basic weight	120 gsm ±5%

ADHESIVE:

A general purpose removable, acrylic based adhesive. The adhesive features good tack and adhesion in combination with superior and clean removability from most substrates. it has long term removability and the adhesive allows label application at a wide temperature range, retaining its removable properties even at very low temperatures.

Initial Tack	Low
Final Adhesion	Low
Min. App.Temp	-15°C
Temp Range	-30°C to +80°C
UV Resistance	Good

Complies with FDA 175.105 and with BgVV XIV recommendations for direct contact with dry and moist non-fatty foodstuff.

The adhesive may safely stand in direct contact with dry, moist and fatty foodstuffs which have a reduction factor of at least 2 according to the Commission Regulation (EU) No 10/2011.

LINER:

A white, supercalendered glassine paper.

Thickness 53 micron ± 5%

Basic Weight 59 gsm ±5%

SHELF LIFE:

2 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.



Unit A2, Hubert Road, Brentwood, Essex CM14 4JE

Sales sales@bakermaterials.co.uk Labels 01277 281900

Materials

01277 281910

BakPac 01277 281930

bakermaterials.co.uk

ED Director: S R Baker. Company Reg No: 1116854 in England. Registered Office: Unit A2 Hubert Road, Brentwood, Essex CM14 4JE. VAT Reg No: GB 230 7578 65